

PA 1117633

REC'D 01 NOV 2004

WFO PSI NO/IB

1804/52222

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

January 23, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/517,059

FILING DATE: November 04, 2003

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)



**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**

**P. SWAIN
Certifying Officer**

BEST AVAILABLE COPY

110403
14461 U.S. PTO

Please type a plus sign (+) inside this box → 

PTO/SB/18 (02-01)
Approved for use through 10/31/2002. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label No. EV312 069613 Date of Dep sit: NOVEMBER 4, 2003

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
MICHEL A. ERNO H.A.		KLOMPENHOUWER LANGENDIJK		BRED, THE NETHERLANDS EINDHOVEN, THE NETHERLANDS	
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
SMART CLIPPER FOR MOBILE DISPLAYS					
CORRESPONDENCE ADDRESS					
Direct all correspondence to:					
<input checked="" type="checkbox"/> Customer Number <u>24737</u> → <div style="border: 1px solid black; padding: 5px; display: inline-block;">*24737*</div>					
OR Type Customer Number here					
<input type="checkbox"/> Firm or Individual Name		PHILIPS ELECTRONICS NORTH AMERICA CORPORATION			
Address		345 SCARBOROUGH ROAD			
City		BRIARCLIFF MANOR		State	NY
Country		USA		ZIP	10510
		Telephone	(914) 333-9624		Fax (914) 332-0615
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		<u>13</u>		<input type="checkbox"/> CD(s), Number <u> </u>	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets		<u>10</u>		<input type="checkbox"/> Other (specify) <u> </u>	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number: <u>14-1270</u>					
FILING FEE AMOUNT (\$) <u>160.00</u>					
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,
SIGNATURE

TYPED or PRINTED NAME

TELEPHONE

DANIEL J. PIOTROWSKI

(914) 333-9624

Date NOVEMBER 4, 2003

REGISTRATION NO.: 42,079
(if appropriate)

Docket Number: US030436

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C., 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

110403
60/517059

SMART CLIPPER FOR MOBILE DISPLAYS

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to color displays in mobile devices. In particular, the present invention relates to color rendering in mobile displays with limited color gamut. Most particularly, the present invention relates to an apparatus and method for primary color correction and clipping that is especially directed to displays with limited color gamut.

10

2. Description of the Related Art

 In regular displays the color gamut is smaller than the gamut of the human visual system. This means that some colors that we can see cannot be shown on such a display. Especially in mobile (reflective) displays the gamut is small in order to get as much
15 brightness as possible out of the display. Typically the displays cover less than 36% of the gamut set by the European Broadcast Union (EBU).

 FIG. 2 is an example of an EBU display and FIG. 3 is an example of a mobile display having primaries with a saturation of 60% of the saturation of EBU primaries (which is 36% EBU gamut), both with the same brightness. The problem is obvious, the
20 mobile display has poor color rendering in this example.

 There are a number of possible solutions: other color filters and gamut mapping, which can be divided into gamut correction and clipping.

 One solution to the gamut problem could be to increase the gamut of the display by making the color filters thicker, i.e. make them more saturated by blocking more
25 wavelengths. Of course in an LCD display this will reduce the brightness. In the case of a display with ideal color filters the brightness drops by 30%, but in the case of a typical mobile display the brightness drop is more than 50%, as illustrated in FIG. 4 v. FIG. 5.

 On a desktop monitor the display with the large color gamut, FIG. 3, might still be preferred, but if the brightness of the desktop monitor is reduced to 5-10% of the ambient
30 illumination, which approximates a mobile display in a light environment, preference shifts to the brighter display illustrated in FIG. 4 because a lot of detail is missed on the less bright panel illustrated in FIG. 5.

SUMMARY OF THE INVENTION

The present invention provides an algorithm to perform Gamut mapping (primary color correction and clipping), particularly for displays with a smaller color gamut than the incoming video signal, such as mobile displays, by trading-off between color gamut and brightness. The essence of the present invention is to use a high brightness small color gamut mobile display and perform a gamut correction on the incoming RGB signal before sending it to the display drivers. This means that, instead of accepting less saturated primaries for the red (R), green (G) and blue (B) signals and thus de-saturating all colors, the RGB signal is corrected for the new primaries. Now, the colors of the input signal that can be represented on the display are not affected, but as a result of this correction, colors that cannot be represented have to be mapped to a color inside the gamut.

Thus, the present invention comprises:

1. a primary color conversion; and
2. a gamut mapping for colors outside the display gamut.

The foregoing and other features and advantages of the invention will be apparent from the following, more detailed description of preferred embodiments as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a simplified block diagram of a mobile device having a graphics module including the gamut mapping with smart clipping according to the present invention;

FIG. 2 illustrates an EBU standard display;

FIG. 3 illustrates a typical prior art mobile display, which is optimized for brightness at the expense of color gamut by using broad-band color filters;

FIG. 4 illustrates a mobile display optimized for brightness at the expense of color gamut by using broad-band color filters;

FIG. 5 illustrates a mobile display optimized for color gamut at the expense of brightness by using narrow-band color filters;

FIG. 6 illustrates a mobile display of a Portrait image optimized for brightness at the expense of color gamut by using broad-band color filters;

FIG. 7 illustrates the effect of using gamut correction of the incoming signal for the images illustrated in FIG. 3 and 6;

FIG. 8 illustrates a mobile display of a Parrots image optimized for brightness;

FIG. 9 illustrates the image of FIG. 7 with a gamut correction of the incoming signal; (note the clipping artifacts on the red head and the yellow breast).

FIG. 10 illustrates a mobile display optimized for brightness;

FIG. 11 illustrates the display of FIG. 8 with a gamut correction and a brightness reduction of the incoming signal;

FIG. 12 illustrates a mobile display optimized for brightness;

FIG. 13 illustrates the mobile display of FIG. 8 corrected with a smart clipper according to a preferred embodiment of the present invention;

FIG. 14 illustrates a matlab script implementing gamut mapping with 'smart' clipping, according to a preferred embodiment of the present invention;

FIG. 15 illustrates a modification to the matlab script of FIG. 14 that implements peaking according to an alternative preferred embodiment of the present invention;

FIGs. 16 A-D compare an original EBU display A with a conventional 85% EBU display B with the smart clipping of the present invention applied to the conventional EBU display C and with both smart clipping and peaking of the present invention applied to the conventional EBU display D; and

FIG. 17 illustrates the matlab script of gamut mapping, 'smart clipping' and smart brightness reduction of FIG. 15 further modified for saturation calculation.

DETAILED DESCRIPTION OF THE INVENTION

It is to be understood by persons of ordinary skill in the art that the following descriptions are provided for purposes of illustration and not for limitation. An artisan understands that there are many variations that lie within the spirit of the invention and the scope of the appended claims. Unnecessary detail of known functions and operations may be omitted from the current description so as not to obscure the present invention.

Referring to FIG. 1A, the graphics processor 101 of a mobile display 104 may be modified to perform gamut mapping with smart clipping of an input RGB signal 101 according to a preferred embodiment of the present invention. The resultant RGB signal with "smart" clipping 103 is displayed on the mobile display 104. In this preferred embodiment, the functionality of the gamut mapping with "smart" clipping can be

implemented in software or hardware within the graphics processor 101. In an alternative preferred embodiment, illustrated in FIG. 1B, the gamut mapping with "smart" clipping is applied by a dedicated chip 105 to the output signal of a graphics processor 102 and both the graphics processor 102 and dedicated chip 105 are on-board a mobile device with a display 104. Although the description may refer to terms commonly used in describing particular mobile display devices, the description and concepts equally apply to other processing systems, including systems having architectures dissimilar to that shown in FIGs. 1A and 1B.

FIG. 1C illustrates 'smart' clipper either on-board the graphics processor 102 of a mobile device or as a standalone chip 105 therein. The 'smart' clipper includes a controller/processor unit 106 that processes instructions, performs calculations and manages the flow of information and images from and to the network interface 113 and from and to the mobile device display 104. Additionally, the controller/processor 106 is communicatively coupled with a program memory 107. Included within the program memory 107 are a multi-step 'smart' clipper module 108 that controls the selection and execution of algorithms: gamma correction algorithms 109, gamut mapping algorithms 110, smart clipping algorithms 111, and peaking algorithms 112. The controller/processor 106 may also manage the network interface 113 for acquiring the digital image data and directing its processing by the multi-step 'smart' clipper module 108 and display on the mobile display 104. Additionally, the controller/processor 106 may store the original and processed digital image data in a data memory (not shown) to allow local editing, redisplay and retransmission over the network of these images. Notably, the network can be a wireless network or wired network.

How to transform a signal that is represented by one set of primary color points, to another set of primaries, is well known in the art. Consider an incoming video signal RGB_1 (column with Red, Green, and Blue). Let A_1 be a 3×3 matrix, having in each column the tri-stimulus values (X,Y,Z) of the R(ed), G(reen), and B(lue) primaries of an EBU calibrated display. Let A_2 be a similar matrix for a mobile display with limited gamut. Then, the matrix multiplication:

30

$$RGB_2 = (A_2)^{-1} * A_1 * RGB_1 \quad (Eq.1)$$

converts the signal from the EBU primaries to the display primaries. For a low-saturation mobile display having primaries with incorrect hue this is equivalent to a saturation increase (expansion) and a hue correction of the input signal such that it shows the same colors on the mobile display as the EBU display for colors that are within its gamut. The colors outside its gamut cannot be represented, and have to be mapped to a value inside the gamut. In this mapping process, there are a lot of possibilities.

The simplest form of this mapping, 'clipping', where it is assumed that the display signals range from 0 to 1, is as follows:

10 for each pixel (R,G,B) perform the following mapping

$$R(\text{if } R < 0) = 0, G(\text{if } G < 0) = 0, B(\text{if } B < 0) = 0 \quad (\text{Eq. 2})$$

$$R(\text{if } R > 1) = 1, G(\text{if } G > 1) = 1, B(\text{if } B > 1) = 1 \quad (\text{Eq. 3})$$

15 However, clipping can lead to visible artifacts, (color shifts) and the following algorithm performs better:

$$R(R < 0) = 0, G(G < 0) = 0, B(B < 0) = 0 \quad (\text{Eq. 2'})$$

$$R(R > 1) = R(R > 1) / \max(R, G, B),$$

$$G(G > 1) = G(G > 1) / \max(R, G, B), \text{ and}$$

$$20 \quad B(B > 1) = B(B > 1) / \max(R, G, B) \quad (\text{Eq. 3'})$$

reducing the saturation by setting negative values to zero and reducing the brightness by scaling with the maximum (R,G,B). This effectively clips the color along a line to the black-point ('clip to black'). The hue will not change.

In comparing images illustrated in FIG. 6 v. FIG. 7 the improvement is quite striking, yet, in other images such as the 'Parrots' illustrated FIG. 8 v. FIG. 9, the gamut correction and subsequent mapping result in very annoying clipping artifacts. The difference between the Portrait images of FIGs. 6 and 7 and the Parrot images of FIGs. 8 and 9 is that the Portrait mapping has most colors within the gamut of the mobile display, whereas the Parrot mapping has many colors outside of the color gamut of the mobile display. One can see that the out-of-gamut pixels in the head of the red parrot clip to almost the same red color, and similarly for the yellow, which leads to a loss of texture in these areas.

Gamut Mapping With Brightness Reduction

In order to prevent the clipping artifacts of the gamut correction, one can combine it with a brightness reduction. In this way brightness is exchanged back for color again, but now “digitally” instead of “physically”. This prevents a (possibly large) number of pixels with different colors being mapped to the same color, but as a consequence, colors inside the gamut are affected too. This is generally referred to as ‘soft-clipping’, and the amount of ‘soft-clipping’ can always be combined with (the remaining amount of) ‘hard-clipping’ to find a good tradeoff between clipping artifacts and brightness reduction. Brightness reduction only prevents clipping for colors that contain an RGB value that exceeds the maximum, but since these are (by definition) bright pixels, the effect of reducing the clipping artifacts here, can be large.

In a preferred embodiment, the brightness reduction is accomplished by multiplying all pixel values in the image with a factor between 0 and 1. After some trial and error a factor of 0.85 appears to provide good results for the images tested (n=10) on a mobile LCD display. As can be seen in FIGs. 10 and 11 the clipping artifacts have disappeared, but the image is a little less bright.

Gamut Mapping With Smart Clipping

In a preferred embodiment, a solution is based on the perceptual attribute “colorfulness”, which is based on the rule-of-thumb that images that are brighter seem to possess more color. In the smart clipping algorithm of a preferred embodiment, a brightness reduction is followed by a gamut (primary) correction but instead of performing a hard clip on the out-of-gamut values (by clipping values smaller than 0 to zero) a smart clip is performed by “adding white” to the out-of-gamut pixels only. This reduces the saturation but at the same time it increases the brightness. In other words, in a preferred embodiment, the saturation is decreased in favor of increased brightness, which gives similar colorfulness on a mobile display as on an EBU display. This smart clipping affects those colors that cannot be represented because one of the RGB values is smaller than zero.

The algorithm of this preferred embodiment is as follows:

- correct for the low-saturation gamut.
- for pixels with one of R,G,B smaller than 0 the minimum R,G,B value is subtracted from the R,G,B (e.g. (255,200,-10) - -10 = (265,210,0)).

Now, there are no values lower than 0, but still there can be values larger than 255.

- a 'clip to black' is performed on the pixels with one R,G,B larger than 255 (e.g. $(265,210,0) \Rightarrow (265,210,0) * 255 / 265 = (255,202,0)$).

FIG. 13 illustrates the final result of employing a "smart clipper" to the mobile display of
5 FIG. 12, which has only been optimized for brightness.

In an alternative preferred embodiment, in order to prevent a reduction in contrast, the "adding of white" is scaled with the brightness of the pixel such that dark pixels get less white added than bright pixels.

Clipping can be performed by keeping at least one of the color characteristics
10 (luminance, hue, saturation, lightness, colorfulness, etc) constant during the clipping. One way to accomplish this, is to transform the signal to a different space (with some perceptually meaningful coordinates), and perform the clipping in that space. Another method is to use look-up tables. These methods have the disadvantage that they require many operations (e.g. non-linear 'gamma' correction), which is not efficient for mobile
15 applications. Therefore, the preferred 'smart-clipping' method is really an efficient and effective method to render high quality color images on low-quality mobile displays. Especially in the case where the primary colors of the display have roughly the same hue, but lower saturation than the EBU primaries, a simple mapping algorithm of a preferred embodiment the present invention has the advantage that it does not introduce serious color
20 artifacts (color and hue shifts).

FIG. 14 illustrates a matlab script that performs the gamut mapping and 'smart-clipping' color correction. FIGs. 16A-C illustrate the advantage of this embodiment in the appearance of a mobile image. FIG. 16A is a conventional EBU image, FIG. 16B is a mobile display having 85% EBU saturation, FIG. 16C is the mobile display of the image of
25 FIG. 16B modified according to the gamut mapping+smart clipping embodiment of the present invention.

Gamut Mapping With Smart Clipping And Smart brightness reduction

In an alternative preferred embodiment, smart clipping is combined with smart
30 brightness reduction. FIG. 15 illustrates a matlab script that implements this alternative embodiment of gamut mapping, 'smart clipping' and smart brightness reduction.

FIGs. 16A-D illustrate the advantage of this alternative embodiment for a mobile display. FIG. 16A is a conventional EBU image, FIG. 16B is a typical mobile display having 85% EBU saturation, FIG. 16C is the mobile display of the image of FIG. 16B modified according to the gamut mapping+smart clipping embodiment of the present invention, and FIG. 16D is the mobile display of image of FIG. 16B modified according to the gamut mapping+smart clipping+smart brightness reduction embodiment of the present invention.

Smart brightness reduction can also be referred to as saturation dependent attenuation. FIG. 17 illustrates the matlab script of gamut mapping, 'smart clipping' and smart brightness reduction further modified for saturation calculation.

While the preferred embodiments of the present invention have been illustrated and described, it will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the present invention. In addition, many modifications may be made to adapt the teaching of the present invention to a particular situation without departing from its central scope. Therefore it is intended that the present invention not be limited to the particular embodiments disclosed as the best mode contemplated for carrying out the present invention, but that the present invention include all embodiments falling within the scope of the appended claims.

What is claimed is:

1. A method for correcting a color image, the method comprising the steps of:
correcting the gamut of the color image; and
smart clipping the corrected image by "adding white" to out-of-gamut digital data of the color image.
2. The method of claim 1, wherein the smart clipping step of "adding of white" further comprises the step of scaling with the brightness of digital data having dark digital data get less white added than bright digital data.
3. The method of claim 1, further comprising the step of reducing overall brightness of the color image.
4. The method of claim 3, wherein said reducing step further comprises the step of multiplying digital image data of the color image by a fixed value of 0.85.
5. The method of claim 3, wherein said reducing step further comprises the step of determining the reduction as a function of an input gamut and a display gamut.
6. The method of claim 3, wherein said reducing step further comprises the step of determining the reduction as a function of a saturation of the incoming signal.
7. The method of claim 6, wherein said function is 0 when the saturation is equal to 0, maximal when the saturation greater than 0.75, and equal to a monotonically increasing function as a function of the saturation when the saturation is in the range between 0 and 0.75.
8. The method of claim 1, further comprising the steps of:
optionally performing a gamma correction on the digital image data before the step of correcting the gamut; and
if needed, performing an inverse gamma correction on the smart clipped image.

9. The method of claim 8, further comprising the step of reducing the overall brightness of the color image.

10. The method of claim 9, wherein said reducing step further comprises the step of determining the reduction as a function of a saturation of the incoming signal.

11. The method of claim 10, wherein said function is 0 when the saturation is equal to 0, maximal when the saturation greater than 0.75, and equal to a monotonically increasing function as a function of the saturation when the saturation is in the range between 0 and 0.75.

12. An apparatus for primary color correction and clipping, comprising:

a means for receiving digital data of a color image having a source gamut;

a display having a display gamut;

one of a program memory storing and a calculation logic device providing-

(i) a plurality of algorithms, that includes smart clipping algorithms, for mapping the source gamut to the display gamut, and

(ii) a multi-step 'smart' clipper module that executes the plurality of algorithms for mapping the source gamut to the display gamut; and

a controller/processing unit configured to -

control receipt of the digital data,

execute the 'smart' clipper module to accomplish mapping the source gamut to the display gamut for the received digital data, and

output the mapped digital data to the display.

13. The apparatus of claim 12, further comprising a storage device for storing received digital data and output digital data of a color image.

14. The apparatus of claim 13, wherein the plurality of algorithms comprises:

optionally executable gamma correction algorithms;

gamut mapping algorithms to reduce brightness of digital data of a color image;

smart clipping algorithms to correct digital data of a color image by "adding white" to out-of-gamut digital data of the color image; and

saturation dependent attenuation algorithms.

15. The apparatus of claim 13, wherein the smart clipping algorithms further comprise magnifying the clipping effect based on intensity of digital data of the color image.

16. The apparatus of claim 12, wherein the plurality of algorithms comprises:
optionally executable gamma correction algorithms;
gamut mapping algorithms to reduce brightness of digital data of a color image;
smart clipping algorithms to correct digital data of a color image by "adding white" to out-of-gamut digital data of the color image; and
saturation dependent attenuation algorithms.

17. The apparatus of claim 16, wherein the smart clipping algorithms further comprise magnifying the clipping effect based on intensity of digital data of the color image.

18. A 'smart' clipper apparatus for primary color correction and clipping, comprising:
a plurality of algorithms, that includes smart clipping algorithms, for mapping a source
gamut to a display gamut, and
a multi-step 'smart' clipper module that executes said plurality of algorithms.

19. The 'smart' clipper apparatus of claim 18, wherein the plurality of algorithms comprises:
optionally executable gamma correction algorithms;
gamut mapping algorithms to reduce brightness of digital data of a color image;
smart clipping algorithms to correct digital data of a color image by "adding white" to out-of-gamut digital data of the color image; and
saturation dependent attenuation algorithms.

20. The 'smart' clipper apparatus of claim 19, wherein the smart clipping algorithms further comprise magnifying the clipping effect based on intensity of digital data of the color image.

21. A computer readable medium, comprising computer instructions for:
a plurality of algorithms, that includes smart clipping algorithms, for mapping a
source
gamut to a display gamut, and
a multi-step 'smart' clipper module that executes said plurality of algorithms.

22. The computer readable medium of claim 21, wherein said plurality of
algorithms further comprises computer instructions for:
optionally executable gamma correction algorithms;
gamut mapping algorithms to reduce brightness of digital data of a color image;
smart clipping algorithms to correct digital data of a color image by "adding white" to
out-of-gamut digital data of the color image; and
saturation dependent attenuation algorithms.

23. The computer readable medium of claim 22, wherein the smart clipping
algorithms further comprise magnifying the clipping effect based on intensity of digital data
of the color image.

ABSTRACT OF THE DISCLOSURE

An apparatus and method for primary color correction and clipping is provided that is particularly suited for application in mobile displays. It is a combination of a brightness reduction, and a 'smart' clipping algorithm and is based on the perceptual attribute "colorfulness", in which images that are brighter seem to possess more color. In the smart clipping algorithm, a brightness reduction is followed by a gamut (primary) correction and then a smart clip is performed by "adding white" to the out-of-gamut pixels only. This reduces the saturation while it increases the brightness. That is, the saturation is decreased in favor of increased brightness, which gives similar colorfulness on a mobile display as on an EBU display. This smart clipping affects those colors that cannot be represented on the display.




FIG. 1A




FIG. 1B




FIG. 1C



FIG. 2

FIG. 3



FIG. 4

FIG. 5



FIG. 6



FIG. 7



FIG. 8



FIG. 9




FIG. 10

FIG. 11




FIG. 12

FIG. 13


```

% Assume input image is  $0 < (R,G,B) < 1$ 

% Constants
MIN = 0                      (typically 0 or 16/255)
MAX = 1                      (typically 1 or 235/255)

IMAXFAC = g(A1,A2)  (reduce overall brightness, depends on
input gamut and display gamut, e.g. 0.85)

% Effect size (larger with larger values of R,G,B)
ALPHA = f(R,G,B)  (e.g.  $\max(R,G,B)$  or  $\sqrt{R^2+G^2+B^2}$ , or
 $c_1R+c_2G+c_3B$ )

% Reduce overall brightness
 $(R,G,B) = (R,G,B) * IMAXFAC$ 

% Gamma correction (go to linear color domain, this
% can be omitted for simplification, to reduce the
% number of operations, but the color transformations
% are no longer very accurate)
 $(R,G,B) = (R,G,B)^{GAMMA}$ 

% Gamut correction (expansion)
 $(R,G,B) = inv(A2) * A1 * (R,G,B)$ 

% Clipping values  $< MIN$  if any  $((R,G,B) < MIN)$ , Subtract
% minimum multiplied with certain factor depending on
% intensity
 $(R,G,B) = (R,G,B) + ALPHA * (MIN - \min(R,G,B,MIN))$ 
end

% Clipping values  $> MAX$  if any  $((R,G,B) > MAX)$ ,
% Scale RGB vector within maximum
 $(R,G,B) = (R,G,B) * (MAX / \max(R,G,B,MAX))$ 
end

% Inverse gamma correction, if needed
 $(R,G,B) = (R,G,B)^{(1/GAMMA)}$ 

```

FIG. 14

```

% Assume input image is  $0 < (R,G,B) < 1$ 

% Constants
MIN = 0                (typically 0 or 16/255)
MAX = 1                (typically 1 or 235/255)
IMAXFAC = g(A1,A2)      (reduce overall brightness, depends
on input gamut and display gamut, e.g. 0.85)

% Effect size (larger with larger values of R,G,B)
ALPHA = f(R,G,B)        (e.g.  $\max(R,G,B)$  or  $\sqrt{R^2+G^2+B^2}$ ,
or
                         $c_1R+c_2G+c_3B$ )

% Reduce overall brightness
(R,G,B) = (R,G,B)*IMAXFAC
(R,G,B) = (R,G,B)*F(S);
% Where S is the saturation, that can be calculated from R,G,B
% and F(S) is a function of S that is equal to MAX for S=0 and
% equal to IMAXFAC for S = some (constant) value between 0 and
% the maximum saturation of the primary colors. The function F
% can be any continuously decreasing function, e.g. linear or
%  $\cos^2$ . For the example below S=0.75 is the cut-off
% saturation for which F(S) is IMAXFAC.

% Gamma correction (go to linear color domain, this can be
% omitted for simplification, to reduce the number of
% operations, but the color transformations are no longer very
% accurate)
(R,G,B) = (R,G,B)^GAMMA

% Gamut correction (expansion)
(R,G,B) = inv(A2) * A1 * (R,G,B)

% Clipping values < MIN if any((R,G,B)<MIN),
% Subtract minimum multiplied with certain factor depending on
% intensity
(R,G,B) = (R,G,B) + ALPHA*(MIN - min(R,G,B,MIN))
end

% Clipping values > MAX if any((R,G,B)>MAX),
% Scale RGB vector within maximum
(R,G,B) = (R,G,B) * (MAX/max(R,G,B,MAX))
end

% Inverse gamma correction if needed
(R,G,B) = (R,G,B)^(1/GAMMA)

% Output image is between: MIN<(R,G,B)<MAX

```

FIG. 15

Original:
EBU display



FIG. 16A

Conventional:
EBU85pct



FIG. 16B

Smart Clipping:
EBU85pct



FIG. 16C

Smart Clipping + Peaking:
EBU85pct



FIG. 16D


```

% Assume input image is 0<(R,G,B)<1

% Constants
MIN = 0                      (typically 0 or 16/255)
MAX = 1                      (typically 1 or 235/255)
IMAXFAC = g(A1,A2)          (reduce overall brightness, depends on input gamut
and display gamut, e.g. 0.85)

% Effect size (larger with larger values of R,G,B)
ALPHA = f(R,G,B)            (e.g. max(R,G,B) or  $\sqrt{R^2+G^2+B^2}$ , or
c1R+c2G+c3B)

% Reduce overall brightness
(X)   [0.4306   0.3415   0.1784]   (R)
(Y) = [0.2220   0.7067   0.0713] * (G)
(Z)   [0.0202   0.1296   0.9393]   (B)

u' = 4*X/(X + 15*Y + 3*Z)
v' = 9*Y/(X + 15*Y + 3*Z)

S = 13*sqrt((u'-0.1978).^2+(v'-0.4683).^2);
SCUT = 0.75;
if S>SCUT,
    F = IMAXFAC;
else
    F = (((1+cos(S/SCUT*pi))/2).^2) * (1-IMAXFAC) + IMAXFAC;
end
(R,G,B) = (R,G,B)*F;
% Where S is the saturation, that can be calculated from R,G,B
% and F(S) is a function of S that is equal to MAX for S=0 and
% equal to IMAXFAC for S = some (constant) value between 0 and
% the maximum saturation of the primary colors. The function F
% can be any continuously decreasing function, e.g. linear or
% cos^2. For the example below S=0.75 is the cut-off
% saturation for which F(S) is IMAXFAC.

% Gamma correction (go to linear color domain, this can be
% omitted for simplification, to reduce the number of
% operations, but the color transformations are no longer very
% accurate)
(R,G,B) = (R,G,B)^GAMMA
% Gamut correction (expansion)
(R,G,B) = inv(A2) * A1 * (R,G,B)
% Clipping values < MIN if any((R,G,B)<MIN),
% Subtract minimum multiplied with certain factor depending on
% intensity
(R,G,B) = (R,G,B) + ALPHA*(MIN - min(R,G,B,MIN))
end
% Clipping values > MAX if any((R,G,B)>MAX),
% Scale RGB vector within maximum
(R,G,B) = (R,G,B) * (MAX/max(R,G,B,MAX))
end
% Inverse gamma correction if needed
(R,G,B) = (R,G,B)^(1/GAMMA)

% Output image is between: MIN<(R,G,B)<MAX

```

FIG. 17

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.